


CODE 1004




Raccordo femmina - Female adaptor - Raccord femelle - Enlace rosca hembra - Anschlussverschraubung mit Innengewinde
Муфта с внутренней резьбой



CODE	DIM dxg [mmxin.]	D [mm]	L [mm]	I [mm]	H [mm]	PN [bar]	PACK [UMV]	
							RIF. 2	RIF. 5
1004016002001	16x1/2"	42	69	50	17	16	120	-
1004016003001	16x3/4"	42	73	50	19	16	120	-
1004020002001	20x1/2"	46	77	58	18	16	90	350
1004020003001	20x3/4"	46	79	58	20	16	90	350
1004020004001	20x1"	46	81	58	22	16	70	300
1004025002001	25x1/2"	55	84	65	18	16	50	220
1004025003001	25x3/4"	55	86	65	20	16	50	220
1004025004001	25x1"	55	88	65	22	16	50	200
1004032002001	32x1/2"	63	92	71	18	16	30	150
1004032003001	32x3/4"	63	94	71	20	16	30	150
1004032004001	32x1"	63	96	71	22	16	30	150
1004032005001	*32x1"1/4	63	97	71	23	16	30	140
1004040004001	40x1"	80	110	81	20	16	20	85
1004040005001	*40x1"1/4	80	112	81	22	16	20	85
1004040006001	*40x1"1/2	80	113	81	23	16	20	85

>>>



>>>

CODE	DIM dxg [mmx in.]	D [mm]	L [mm]	I [mm]	H [mm]	PN [bar]	PACK [UMV]	
							RIF. 2	RIF. 5
1004051004001	*50x1"	96	140	117	20	16	-	45
1004051005001	*50x1"1/4	96	144	112	22	16	-	45
1004051006001	*50x1"1/2	96	144	112	23	16	-	45
1004051007001	*50x2"	96	149	111	27	16	-	40
1004064005001	*63x1"1/4	115	159	121	23	16	-	28
1004064006001	*63x1"1/2	115	160	121	28	16	-	28
1004064007001	*63x2"	115	165	121	22	16	-	28
1004064008001	*63x2"1/2	115	168	121	23	16	-	26
1004076007001	*75x2"	129	182	137	28	16	-	18
1004076008001	*75x2"1/2	129	187	137	33	16	-	18
1004076009001	*75x3"	129	187	137	33	16	-	17
1004091007001	*90x2"	155	190	152	26	16	-	11
1004091008001	*90x2"1/2	155	195	152	33	16	-	10
1004091009001	*90x3"	155	195	152	33	16	-	10
1004091010001	*90x4"	155	204	152	42	16	-	10
1004111009001	*110x3"	183	263	204	40	16	-	6
1004111010001	*110x4"	183	263	204	43	16	-	6

* La bocca filettata è rinforzata da un anello di acciaio inox - * The threaded end is reinforced with a stainless steel ring

* La bouche filetée est renforcée par une bague en acier inox - * La boca filetiada está reforzada por un anillo de acero inox

* Die Gewindeöffnung ist mit einem Ring aus rostfreiem Stahl verstärkt - * Конец резьбы усилен кольцом из нержавеющей стали