Heliflex

WATER CONDUCTION



PRODUCT INFO

DESIGNATION agroflat sl

PRODUCT CODE 210 390

MATERIALS Flexible PVC with textile polyester mesh.

STANDARDS Heliflex internal requirements.



TECHNICAL FEATURES Flexible; Light-weight; Low pressure resistance.



enduring trust

Description

PVC double layer flat hose reinforced with polyester yarns, very lightweight. Mainly used for conveying water at low pressures.

Application Areas:

Mainly for drip irrigation and conveying water at low pressure. Agricultural use; Water conveyance.

Main features:

Layflat hose reinforced with polyester yarn. Light and flexible.

Temperature:

-10/+55°C

Presentation:

Colour: Yellow and Green.

Available in lengths of 25, 50 and 100 meters, depending on the diameters. * Note: Other colours, diameters and lengths available upon request.

Marking:

Heliflex agroflat sl Ømm lote data



Heliflex

WATER CONDUCTION



agroflat sl | 210 390

CODE								
GROUP	INNER Ø	LENGTH	COLOR	OUTER Ø	THICKNESS	WEIGHT	WORK PRESSURE	BURST PRESSURE
	mm	m		mm	mm	kg/m	bar	bar
210 390	025	*	41/19	28,0	1,5	0,170	5,2	13,0
	038	*		41,0		0,255	5,0	12,5
	040	*		42,4	1,4	0,240	5,0	
	050	*		52,8		0,305	5,0	
	055	*		65,4		0,365	5,0	
	063	*		65,4	1,5	0,385	4,5	11,3
	070	*		73,0		0,430	4,5	
	075	*		78,0		0,485	4,0	10,0
	080	*		83,0		0,500	4,0	
	090	*		93,0		0,590	4,0	
	100 (103)	*		106,2	1,6	0,740	3,0	7,5
	110	*		113,0	1,7	0,830	3,0	
	125	*		128,8	1,8	0,880	3,0	
	150	*		153,8	1,9	1,050	3,0	





Cor 41 Cor 19

