



PRODUCT INFO

DESIGNATION
helivil acetileno

PRODUCT CODE
360 234

MATERIALS
Flexible PVC with textile polyester mesh.

STANDARDS
Manufactured in accordance to ISO 3821 standard.



3D



built from safety materials

Description

Flexible PVC hose, reinforced with high-strength polyester mesh. Manufactured according to ISO 3821 standard. Mainly used in conveying acetylene and oxygen gas in welding equipments.

Application Areas:

Conveyance of acetylene gas for welding equipment.
Chemicals conveyance; Industrial use.

Main features:

Flexible hose manufactured in flexible PVC and reinforced with polyester yarns.

Temperature:

-10/+50°C

Presentation:

Colour: Red.

Available in lengths of 25, 50 and 100 metres.*

Note Other colours, diameters and lengths available upon request.

Marking

Heliflex helivil acetileno Ømm Data de fabrico YYYY lote data

TECHNICAL FEATURES
Rubber touch; Flexible.



helivil acetileno | **360 234**

CODE				OUTER Ø	THICKNESS	WEIGHT	WORK PRESSURE	BURST PRESSURE
GROUP	INNER Ø	LENGTH	COLOR					
	mm	m		mm	mm	kg/m	bar	bar
360 234	6	*	21	12,0	3,0	0,120	20,0	60
	8	*		14,0	3,0	0,145		
	10	*		16,4	3,2	0,180		
	12	*		20,0	4,0	0,270		

