Heliflex



PRODUCT INFO

DESIGNATION helivil oxigénio

PRODUCT CODE 360 235

MATERIALS Flexible PVC with textile polyester mesh.

STANDARDS

Manufactured in accordance to ISO 3821 standard.



TECHNICAL FEATURES Rubber touch; Flexible.



built from safety materials

Description

Flexible PVC hose, reinforced with high-strength polyester mesh. Manufactured according to ISO 3821 standard. Mainly used in conveying acetylene and oxygen gas in welding equipments.

Application Areas:

Conveyance of acetylene gas for welding equipment. Chemicals conveyance; Industrial use.

Flexible hose manufactured in flexible PVC and reinforced with polyester yarns. Temperature:

-10/+50°C

Presentation:

Colour: Blue.

Available in lengths of 25, 50 and 100 metres.*

Note Other colours, diameters and lengths available upon request.

Heliflex helivil oxigénio Ømm Data de fabrico YYYY lote data



Heliflex

GASES



helivil oxigénio | 360 235

CODE								
GROUP	INNER Ø	LENGTH	COLOR	OUTER Ø	THICKNESS	WEIGHT	WORK PRESSURE	BURST PRESSURE
	mm	m		mm	mm	kg/m	bar	bar
360 235	6	*	51	12,0	3,0	0,120	20,0	60
	8	*		14,0	3,0	0,145		
	10	*		16,4	3,2	0,180		
	12	*		20,0	4,0	0,270		



